

EQUIP 40

▲SPECIFICATIONS 15inoh 3PIECE/NORMAL

SIZE	STANDARD A - Disk 4H-100 4H-114.3										DEEP RIM O - Disk 4H-100 4H-114.3										BIG GALIPER T - Disk 4H-100 4H-114.3									
	Lip Size (mm)										Lip Size (mm)										Lip Size (mm)									
	45	57	70	82	95	107	120	133	145	158	45	57	70	82	95	107	120	133	145	158	45	57	70	82	95	107	120	133	145	158
15x5.5J	3 A									13 A											-22 A									
15x6.0J	10 B	-3 A								20 B	7 A										-15 B	-28 A								
15x6.5J	16 C	3 B	-9 A							26 C	13 B	1 A									+9 C	-22 B	-34 A							
15x7.0J	22 D	10 C	-3 B	-16 A						32 D	20 C	7 B	-6 A								-3 D	-15 C	-28 B	-41 A						
15x7.5J	29 E	16 D	3 C	-9 B	-22 A					39 E	26 D	13 C	1 B	-12 A							4 E	-9 D	-22 C	-34 B	-47 A					
15x8.0J	35 F	22 E	10 D	-3 C	-16 B	-28 A				45 F	32 E	20 D	7 C	-6 B	-18 A						10 F	-3 E	-15 D	-28 C	-41 B	-53 A				
15x8.5J	41 G	29 F	16 E	3 D	-9 C	-22 B	-35 A			51 G	39 F	26 E	13 D	1 C	-12 B	-25 A					16 G	4 F	-9 E	-22 D	-34 C	-47 B	-60 A			
15x9.0J		35 G	22 F	10 E	-3 D	-16 C	-28 B	-41 A			45 G	32 F	20 E	7 D	-6 C	-18 B	-31 A					10 G	-3 F	-15 E	-28 D	-41 C	-53 B	-66 A		
15x9.5J			29 G	16 F	3 E	-9 D	-22 C	-35 B	-47 A			39 G	26 F	13 E	1 D	-12 C	-25 B	-37 A				4 G	-9 F	-22 E	-34 D	-47 C	-60 B	-72 A		
15x10.0J				22 G	10 F	-3 E	-16 D	-28 C	-41 B	-54 A				32 G	20 F	7 E	-6 D	-18 C	-31 B	-44 A			-3 G	-15 F	-28 E	-41 D	-53 C	-66 B	-79 A	
15x10.5J					16 G	3 F	-9 E	-22 D	-35 C	-47 B					26 G	13 F	1 E	-12 D	-25 C	-37 B				-9 G	-22 F	-34 E	-47 D	-60 C	-72 B	
15x11.0J						10 G	-3 F	-16 E	-28 D	-41 C						20 G	7 F	-6 E	-18 D	-31 C					-15 G	-28 F	-41 E	-53 D	-66 C	
15x11.5J							3 G	-9 F	-22 E	-35 D							13 G	1 F	-12 E	-25 D						-22 G	-34 F	-47 E	-60 D	
15x12.0J								-3 G	-16 F	-28 E								7 G	-6 F	-18 E							-28 G	-41 F	-53 E	
15x12.5J									-9 G	-22 F									1 G	-12 F								-34 G	-47 F	
15x13.0J										-16 G										-6 G										-41 G

- Available finishes: Sprint Gold (SGL) / Brut Silver (BSL)
- Included accessories: (1) center cap (High type or Low type) / (1) valvestem (V29A)
- Black assembly bolts are standard
- ※ Please note with lip size of 32mm, the center cap is protruding 3mm from the rim flange